



Roca

Rockart II



Rockart White Capucchino 2"x4" Oval - 12"x12" Mosaic

NATURAL STONE MOSAIC

Rockart II

A mosaic collection inspired by the organic beauty of natural stone and soft earthy tones. Featuring versatile patterns and timeless textures, each design brings warmth, character, and contemporary elegance to residential and commercial spaces.

Natural Stone Mosaic

◆ ▢ M | 11"x11" 11"x12" 12"x12"

Rockart II

Natural Stone Mosaic



8-10
mm



11"x11"
28x28 cm

11"x12"
28x30 cm

12"x12"
30x30 cm

* Mesh Mounted



Travertine
2"x2" Hex



11"x11"



Travertine 2"x2"
Penny Round



11"x12"



Travertine
2"x4" Oval



12"x12"



White Capuccino
2"x4" Oval



12"x12"



Travertine
Stacked



12"x12"



White Capuccino
Stacked



12"x12"

Rockart II

Natural Stone Mosaic



8-10
mm



12"x12"
30x30 cm

* Mesh Mounted




Platimun White
Chevron



12"x12"



Platinum White
2"x2" Square



12"x12"



Platinum White
2"x3" Hex



12"x12"

Technical Specifications

ITEM	TYPE OF STONE	FINISH	THICKNESS	RECOMMENDED GROUT JOINT	RECOMMENDED TRAFFIC
PLATINUM WHITE CHEVRON 12X12	Glacier White Marble	Sawn, Shot-blast & Tumbled	3/8	2/16	R
PLATINUM WHITE 2X3 HEX 12X12	Glacier White Marble	Sawn & Tumbled	3/8	2/16	R
PLATINUM WHITE 2X2 SQ 12X12	Glacier White Marble	Sawn & Tumbled	1/3	2/16	R
TRAVERTINE STACKED 12X12 MOSAIC	Travertine	Tumbled	1/3	2/16	N/A
TRAVERTINE 2X2 PENNY ROUND 11X12	Travertine	Tumbled	1/3	2/16	N/A
TRAVERTINE 2X4 OVAL 12X12	Travertine	Tumbled	1/3	2/16	N/A
TRAVERTINE 2X2 HEX 11X11	Travertine	Tumbled	1/3	2/16	N/A
WHITE CAPUCCINO 2X4 OVAL 12X12	Mix Cream / Capuccino Marble	Honed	1/3	2/16	M/L
WHITE CAPUCCINO STACKED 12X12	Mix Cream / Capuccino Marble	Honed	1/3	2/16	M/L


ITEM	STONE CHARACTERISTICS	COLOR VARIATION	INTERIOR / EXTERIOR USE	FLOOR / WALL USE	STONE ORIGIN
PLATINUM WHITE CHEVRON 12X12	Group I	CV02	BOTH	F/W	India
PLATINUM WHITE 2X3 HEX 12X12	Group I	CV02	BOTH	F/W	India
PLATINUM WHITE 2X2 SQ 12X12	Group I	CV02	BOTH	F/W	India
TRAVERTINE STACKED 12X12 MOSAIC	Group III	CV02	BOTH	W	Indonesia
TRAVERTINE 2X2 PENNY ROUND 11X12	Group III	CV02	BOTH	W	Indonesia
TRAVERTINE 2X4 OVAL 12X12	Group III	CV02	BOTH	W	Indonesia
TRAVERTINE 2X2 HEX 11X11	Group III	CV02	BOTH	W	Indonesia
WHITE CAPUCCINO 2X4 OVAL 12X12	Group I	CV02	BOTH	F/W	Indonesia
WHITE CAPUCCINO STACKED 12X12	Group I	CV02	BOTH	F/W	Indonesia

Packaging Info

Size	SF per carton	PC per carton	BX per pallet
11"x11"	10.21	13	54
11"x12"	9.95	11	54
12"x12"	9.69	10	45

Natural Stone Mosaics
Installation Instructions

TECHNICAL NOTE Natural stone exhibits inherent variations in shade, texture, and composition. These characteristics are not defects but part of the product’s natural beauty.



INSPECTION

- Inspect all material prior to installation.
- Natural stone mosaics vary in color, size, thickness, and texture.
- Blend sheets from multiple cartons to ensure a balanced appearance.
- Do not install damaged or defective material.
- Installation constitutes acceptance of the product.

SUBSTRATE PREPARATION

- Surface must be clean, dry, structurally sound, and free of contaminants.
- Maximum substrate variation: 1/8”in10 ft (3mm in 3 m).
- Wet areas (showers, floors, exterior applications) require an approved water-proofing membrane compliant with ANSI A118.10.
- Shower floors must have a minimum slope of 1/4”per foot (6 mm per 300mm) toward the drain.

ADHESIVE

- Use a white polymer-modified thin-set mortar meeting ANSI A118.4 or A118.15.
- Recommended trowel: 1/4” x 1/4” square notch, or as needed to achieve full coverage.
- Do not use premixed mastics in wet areas. Avoid excessive mortar between stones.

INSTALLATION

- Carefully align mesh sheets to avoid visible sheet lines.
- Adjust individual chip as needed to create a seamless transition between sheets.
- Press sheets firmly into mortar using a grout float or beating block to ensure even surface contact.
- Remove excess mortar before curing.

GROUTING

- Allow mortar to cure per manufacturer’s recommendations before grouting.
- Use unsanded or fine-grain grout depending on joint width. Due to irregular joints, additional grout may be required.
- Clean thoroughly to prevent grout haze on textured surfaces.

SEALING (REQUIRED)

- Apply a penetrating stone sealer prior to grouting to ease cleanup.
- Seal again after grout has fully cured.
- Periodic resealing is required depending on traffic and exposure.
- Failure to seal may result in staining.

CLEANING & MAINTENANCE

- Use PH-neutral cleaners formulated for natural stone.
- Do not use acidic, abrasive, or bleach-based cleaners.
- Wipe dry in wet environments to minimize mineral deposits.



ATTENTION

Installation must comply with current TCNA Handbook and ANSI A108 standards. Installer is responsible for proper installation practices. Manufacturer assumes no liability for improper installation or lack of sealing.